

Declaration of Performance

System 3 Ltd declare that the Heat Strengthened (HeatStrength) Soda Lime Silicate Glass supplied is intended for use in buildings and construction works.

It is not for use as Bullet or Explosion Proof Glass or
Fire Glazing Specifications unless stated otherwise.

All Heat Strengthened glass conforms to system 3 - EN1863 - 2: 2004 annex ZA.


Type testing to EN1863 has been performed by
BSI Assurance UK Ltd, Kitemark House, Herts, HP2 7PT, UK
Approved Body 0086

Essential Characteristics	Performance	Essential Characteristics	Performance
Resistance to Fire	NPD	Reaction to Fire	A1
External Fire Performance	NPD	Bullet Resistance	NPD
Explosion Resistance	NPD	Burglar Resistance	NPD
Pendulum Body Impact Resistance	NPD	Resistance Against Sudden Temperature Change & Temperature Differentials	100 K
Wind, Snow Permanent & Increased Load Resistance	4mm	Direct Airborne Sound Insulation	29 dB
Thermal Properties	5.8 W/m2K		
<u>Radiation Properties</u>			
Light Transmission & Reflection	0.90/0.08/0.08	Solar Energy Characteristics	0.85/0.08/0.08

The performance of the product identified above is in conformity with the set of detailed performance(s). This declaration of performance is issued, in accordance with Construction Product Regulations 305/2011, under the sole responsibility of the manufacturer identified above as it has effect in the United Kingdom in respect of Great Britain.

4mm Clear Heat Strengthened shown (worst case scenario HeatStrength Single Glass), others available upon request

Signed by: _____



Allan Brown - Director

Date: 11th March 2025